

## KITCHEN'S CRANE & EQUIPMENT

7913 Dunnottar Court, Chesterfield, VA 23838 1-804-814-4844 info@KitchensEquipment.com www.kitchensequipment.com

## 2010 Scheuerle K25 Trailers

Set 1:

TWO K25 module 6-axle including hose set and set steering rods

Set 2:

TWO 2010 Scheuerle K2506

Also available:

1 x Used Drawbar

1 x Used Header

1 x Used Steering Rod

1 x Used PPU

1 x Used Operating panel



























## 4-axle SPMT with 4 driven pendulum axles, M93

No.of Wheel bogies - driven No.of Wheel bogies - braked No.of Wheel bogies - idle Wheel bogies - total

Tractive force approx. Braking force approx. Platform dimensions, (L x W)

Platform height-lowered (loaded)

Platform height-driving pos. (loaded) Axle compensation

Type of steering / steering angle

Frame, bending moment

4 pcs. 0 pcs. 8 pcs.

240 kN 240 kN


5600 mm x 2430 mm

approx. 1150 mm (approx.1180 mm unloaded)

1.500 mm 700 (± 350 mm)

rack and pinion gear / ± 130°

M93, +9250 / -9250



			TT20 (Tube Type) 355 / 65-15 IC 40				TL24 (tubeless) 355 / 65-15 IC 40				PF24 355 / 65-15 IC 40 Polyfilled tires				PF30 355 / 65-15 IC 40 Polyfilled tires			
Payload max. approx.			143,6 t				175,6 t				174,2 t				222,2 t			
Gross weight		160,0 t				192,0 t				192,0 t				240,0 t				
Project dead weight approx.		16,4 t				16,4 t				17,8 t				17,8 t				
Axle load - admissible		40,0 t				48,0 t				48,0 t				60,0 t				
Support Cylinder (D24 max. 24t, D30 max 30t pendulum axle load)		D24				D24				D24				D30				
Operating temperature		-20/+40 °C				-20/+40 °C				-20/+40 °C				-20/+40 °C				
Admissible travel speed	Standard	11,5 km/h				11,5 km/h				11,5 km/h				11,5 km/h				
Admissible travel speed / axle line load for tire:		10 km/h	5 km/h	3 km/h	1 km/h	10 km/h	5 km/h	3 km/h	1 km/h	10 km/h	5 km/h	3 km/h	1 km/h	10 km/h	5 km/h	3 km/h	1 km/h	
Tire pressure 10 bar		27,0 t	30,0 t	32,0 t	40,0 t	27,0 t	30,0 t	32,0 t	40,0 t									
Tire pressure 15 bar						31,2 t	42,0 t	48,0 t	48,0 t									
										31,2 t	36,0 t	40,0 t	48,0 t	31,2 t	46,0 t	52,0 t	60,0 t	

